

500 SERIES

and Models 444 and 680SS

- Oil-Fired, LP- or Natural-Gas-Fired
- 115V/1PH
- Direct-Drive Pump



The **500 Series** delivers rugged, yet affordable, cleaning power for a broad range of applications, from agriculture to building maintenance. The sporty 555SS, with its stainless steel coil skin, is our most popular entry level hot water model—compact, evenly balanced, easy to maneuver, and engineered with the operator in mind. As with the entire Hotsy line, all models in the 500 series are ETL safety certified to UL-1776, with Hotsy pumps backed by a 7-year limited warranty

MODEL	GPM	PSI	HP	VOLT/PH	AMP	FUEL	PUMP	DRIVE	PORTABILITY	HOSE	SHIP WT (lbs)
444	2	1000	1.5	115/1	15	Oil	Comet Axial	Direct	Std	40'	335
555SS	2.2	1300	2	115/1	20	Oil	Hotsy Duplex	Direct	Std	50'	370
558	2.2	1300	2	115/1	18	LP	Hotsy Duplex	Direct	Optional	50'	320
559	2.2	1300	2	115/1	18	NG	Hotsy Duplex	Direct	N/A	50'	330
560SS	2.1	1500	2.3	115/1	20	Oil	Hotsy Triplex	Direct	Std	50'	385
680SS	3.0	1000	2	115/1	20	Oil	Hotsy Triplex	Direct	Std	50'	385

SS=Stainless Steel

OPTIONS

PART NO.	DESCRIPTION
835525	10" Natural Gas- or LP Gas-Fired Draft Diverter, Models 558 & 559
924889	8" Oil-Fired Draft Dampener, Models 444, 555SS, 560SS & 680SS
280771	Portagegear, Models 558 / 771
891113	Propane Tank, 43 lb.

OPTIONS

PART NO.	DESCRIPTION
280588	Float Tank, 555SS (Field Install)
860202	360° Pivot Reel, 100'
860201	360° Pivot Reel, 200'

(Hose Reels fit Models 555SS, 560SS & 680SS)

700 SERIES

and Model 870SS

- Oil-Fired, LP- or Natural-Gas-Fired
- 7-Yr Pump Warranty
- Direct- & Belt-Drive



The **700 Series** offers a nice balance of Hotsy ruggedness and cleaning performance, yet the affordability of an entry-level machine. In addition to the four direct-drive models, this series also offers a belt-drive model that cleans at 3.5 GPM and 2000 PSI. The multiple fuel and electrical options makes the 700 series ideal for meeting the needs of commercial customers. All models are ETL safety certified and feature the Hotsy pump with a 7-year warranty.

MODEL	GPM	PSI	HP	VOLT/PH	AMP	FUEL	PUMP	DRIVE	PORTABILITY	HOSE	SHIP WT (lbs)
770SS	2.8	1500	3	208-230/1	20	Oil	Hotsy Triplex	Direct	Std	50'	435
771	2.8	1500	3	208-230/1	13	LP	Hotsy Triplex	Direct	Optional	50'	415
772	2.8	1500	3	208-230/1	13	NG	Hotsy Triplex	Direct	N/A	50'	415
790SS	2.8	2000	4TEFC	230/1	20	Oil	Hotsy Triplex	Belt	Std	50'	460
790SS-208	2.8	2000	4TEFC	208/1	22	Oil	Hotsy Triplex	Belt	Std	50'	460
795SS*	3.5	2000	5	230/1	24	Oil	Hotsy Triplex	Belt	Std	50'	500
795SS-208*	3.5	2000	5	208/1	27	Oil	Hotsy Triplex	Belt	Std	50'	500
870SS	3.5	2000	5	230/1	27	Oil	Hotsy Triplex	Direct	Std	50'	475

*3450 RPM motor SS=Stainless Steel

OPTIONS

PART NO.	DESCRIPTION
835525	10" Natural Gas- or LP Gas-Fired Draft Diverter, Models 771 & 772
924889	8" Oil-Fired Draft Dampener, Models 770SS, 790SS, 795SS & 870SS
280771	Portagegear, Models 558 / 771
891113	Propane Tank, 43 lb.

OPTIONS

PART NO.	DESCRIPTION
860202	360° Pivot Reel, 100'
860201	360° Pivot Reel, 200'

(Hose Reels fit all 700 Series Models EXCEPT 771SS & 772SS)

900 SERIES

- Choose from Oil-Fired, LP-or Natural Gas-Fired
- Rugged Hotsy Pump with 7-Year Warranty
- Stainless-Steel Coil Skin
- Portable or Stationary
- ETL Safety Certified
- Electronic Ignition (NG and LP Models)

Model 980SS (Shown with optional hose reel)



Model 982SS Natural Gas (Portability not available on gas-fired models)



The **900 Series** takes on the heaviest of industrial cleaning jobs. Built with Hotsy ruggedness throughout, the 24 models provide a broad selection of fuel and electrical options—delivering the cleaning power of 3.9 GPM @2000 PSI or 3.8 GPM @ 2300 PSI. Oil-heated models come with a wheel kit for on-site portability. The 900 series of hot water pressure washers are backed by a market-leading 7-year warranty on the Hotsy pump.

MODEL	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMP	FUEL	PUMP	DRIVE	PORTABILITY	HOSE	SHIP WT (lbs)
980SS	3.9	2000	5	1725	230/1	29	Oil	Hotsy Triplex	Belt	Std	50'	580
981SS	3.9	2000	5	1725	230/1	25	LP	Hotsy Triplex	Belt	N/A	50'	550
982SS	3.9	2000	5	1725	230/1	25	NG	Hotsy Triplex	Belt	N/A	50'	550
990SS	3.9	2000	5	1725	230/3	19	Oil	Hotsy Triplex	Belt	Std	50'	580
990SS-208	3.9	2000	5	1725	208/3	20	Oil	Hotsy Triplex	Belt	Std	50'	580
991SS	3.9	2000	5	1725	230/3	16	LP	Hotsy Triplex	Belt	N/A	50'	545
991SS-208	3.9	2000	5	1725	208/3	18	LP	Hotsy Triplex	Belt	N/A	50'	545
992SS	3.9	2000	5	1725	230/3	16	NG	Hotsy Triplex	Belt	N/A	50'	545
992SS-208	3.9	2000	5	1725	208/3	18	NG	Hotsy Triplex	Belt	N/A	50'	545
993SS	3.9	2000	5	1725	460/3	10	Oil	Hotsy Triplex	Belt	Std	50'	580
994SS	3.9	2000	5	1725	460/3	8	LP	Hotsy Triplex	Belt	N/A	50'	545
995SS	3.9	2000	5	1725	460/3	8	NG	Hotsy Triplex	Belt	N/A	50'	545
950SS	3.8	2300	6.2	3450	230/1	30	Oil	Hotsy Triplex	Belt	Std	50'	590
950SS-208	3.8	2300	6.2	3450	208/1	33	Oil	Hotsy Triplex	Belt	Std	50'	590
952SS	3.8	2300	6.2	3450	230/1	27	NG	Hotsy Triplex	Belt	N/A	50'	560
952SS-208	3.8	2300	6.2	3450	208/1	28	NG	Hotsy Triplex	Belt	N/A	50'	560
960SS	3.8	2300	6.2	3450	230/3	19	Oil	Hotsy Triplex	Belt	Std	50'	580
960SS-208	3.8	2300	6.2	3450	208/3	20	Oil	Hotsy Triplex	Belt	Std	50'	580
962SS	3.8	2300	6.2	3450	230/3	17	NG	Hotsy Triplex	Belt	N/A	50'	550
962SS-208	3.8	2300	6.2	3450	208/3	18	NG	Hotsy Triplex	Belt	N/A	50'	550
963SS	3.8	2300	6.2	3450	460/3	9	Oil	Hotsy Triplex	Belt	Std	50'	580
964SS	3.8	2300	6.2	3450	460/3	7	NG	Hotsy Triplex	Belt	N/A	50'	550
967SS	3.8	2300	6.2	3450	575/3	9	Oil	Hotsy Triplex	Belt	Std	50'	580
969SS	3.8	2300	6.2	3450	575/3	7	NG	Hotsy Triplex	Belt	N/A	50'	550

OPTIONS	
PART NO.	DESCRIPTION
280495	Primary Remote Station (1st Remote)
216722	Additional Remote Station(s). Use for Additional Remotes After Primary Remote
280515	Remote Soap Option – Requires Remote Station Option, use on first remote station. Purchase additional switch – P/N 875985 and field wire for each additional remote station.
480400	Auto Start/Stop Kit (Factory Installed)
480401	Thermal Shutdown Kit (Factory Installed)
480404	Time Delay Shutdown (Factory Installed)
480403	LP Conversion-Series: 952SS, 962SS, 964SS & 969SS (Factory Installed)
835526	8" Natural Gas- or LP Gas-Fired Draft Diverter (Gas-fired models only)
924889	8" Oil-Fired Draft Dampener (Oil-fired models only)
7-1010	Regulator, LP Assembly
93-9001400	Portage Kit (Oil-fired models only)
860202	360° Pivot Reel, 100' (Hose Reel fits all 900 Series Models)
860201	360° Pivot Reel, 200' (Hose Reel fits all 900 Series Models)

1400 SERIES

- Oil-Fired, LP-or Natural Gas-Fired
- Belt-Drive Hotsy Pump
- Stainless Steel Coil Skin
- ETL Safety Certified
- Electronic Ignition (NG and LP Models)



1410SS



Model 1412SS (Shown with optional hose reel. Portability not available on gas fired models)

The **1400 Series** packs the biggest punch of Hotsy's portable, electric-powered hot water pressure washers with a cleaning force of 3.9 GPM and 3000 PSI. Powered by a 7.5 HP, 1725 RPM or 8.2 HP, 3450 RPM Baldor motor with 24 configurations, including portable and stationary models, the 1400 series offers hours of non-stop heavy-duty cleaning of everything from trucks to heavy equipment. Besides its ruggedness, the 1400 series is also ETL certified to the rigid UL-1776 safety standards. All models come standard with a stainless steel coil skin.



MODEL	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMP	FUEL	PUMP	DRIVE	PORTABILITY	HOSE	SHIP WT (lbs)
1410SS	3.9	3000	7.5	1725	230/1	37	Oil	Hotsy Triplex	Belt	Std	50'	640
1411SS	3.9	3000	7.5	1725	230/1	34	LP	Hotsy Triplex	Belt	N/A	50'	610
1412SS	3.9	3000	7.5	1725	230/1	34	NG	Hotsy Triplex	Belt	N/A	50'	610
1420SS	3.9	3000	7.5	1725	230/3	25	Oil	Hotsy Triplex	Belt	Std	50'	640
1420SS-208	3.9	3000	7.5	1725	208/3	25	Oil	Hotsy Triplex	Belt	Std	50'	640
1421SS	3.9	3000	7.5	1725	230/3	24	LP	Hotsy Triplex	Belt	N/A	50'	605
1421SS-208	3.9	3000	7.5	1725	208/3	24	LP	Hotsy Triplex	Belt	N/A	50'	605
1422SS	3.9	3000	7.5	1725	230/3	24	NG	Hotsy Triplex	Belt	N/A	50'	605
1422SS-208	3.9	3000	7.5	1725	208/3	24	NG	Hotsy Triplex	Belt	N/A	50'	605
1423SS	3.9	3000	7.5	1725	460/3	14	Oil	Hotsy Triplex	Belt	Std	50'	640
1424SS	3.9	3000	7.5	1725	460/3	12	LP	Hotsy Triplex	Belt	N/A	50'	605
1425SS	3.9	3000	7.5	1725	460/3	12	NG	Hotsy Triplex	Belt	N/A	50'	605
1450SS	3.9	3000	8.2	3450	230/1	40	Oil	Hotsy Triplex	Belt	Std	50'	650
1450SS-208	3.9	3000	8.2	3450	208/1	44	Oil	Hotsy Triplex	Belt	Std	50'	650
1452SS	3.9	3000	8.2	3450	230/1	40	NG	Hotsy Triplex	Belt	N/A	50'	620
1452SS-208	3.9	3000	8.2	3450	208/1	42	NG	Hotsy Triplex	Belt	N/A	50'	615
1460SS	3.9	3000	8.2	3450	230/3	24	Oil	Hotsy Triplex	Belt	Std	50'	645
1460SS-208	3.9	3000	8.2	3450	208/3	25	Oil	Hotsy Triplex	Belt	Std	50'	645
1462SS	3.9	3000	8.2	3450	230/3	22	NG	Hotsy Triplex	Belt	N/A	50'	615
1462SS-208	3.9	3000	8.2	3450	208/3	23	NG	Hotsy Triplex	Belt	N/A	50'	645
1463SS	3.9	3000	8.2	3450	460/3	12	Oil	Hotsy Triplex	Belt	Std	50'	645
1464SS	3.9	3000	8.2	3450	460/3	11	NG	Hotsy Triplex	Belt	N/A	50'	615
1467SS	3.9	3000	8.2	3450	575/3	11	Oil	Hotsy Triplex	Belt	Std	50'	645
1469SS	3.9	3000	8.2	3450	575/3	10	NG	Hotsy Triplex	Belt	N/A	50'	615

OPTIONS	
PART NO.	DESCRIPTION
280495	Primary Remote Station (1st Remote)
216722	Additional Remote Station(s). Use for Additional Remotes After Primary Remote.
280515	Remote Soap Option – Requires Remote Station Option, use on first remote station. Purchase additional switch – P/N 875985 and field wire for each additional remote station.
480401	Thermal Shutdown Kit (Factory Installed)
480404	Time Delay Shutdown (Factory Installed)
480403	LP Conversion-Series: 1452SS, 1462SS, 1464SS & 1469SS (Factory Installed)
480400	Auto Start/Stop Kit (Factory Installed)
835526	8" Natural Gas- or LP Gas-Fired Draft Diverter (Gas-fired models only)
924889	8" Oil-Fired Draft Dampener (Oil-fired models only)
93-9001400	Portagear Kit (Oil-fired models only)
860202	360° Pivot Reel, 100' (Hose Reel fits all 1400 Series Models)
860201	360° Pivot Reel, 200' (Hose Reel fits all 1400 Series Models)

1800 SERIES



1812SS

- Natural Gas or LP-Fired
- Efficient: 510,000 BTU
- 7-Year Pump Warranty

- Electronic Ignition ■ Time Delay Shutdown ■ Thermal Shutdown ■ Remote Ready

The **1800 Series** is a compact, affordable solution for cleaning with hot water indoors. The 12 stationary models are electric-driven and natural gas or LP gas-heated, using Hotsy's high-efficiency vertical hot water coil. The coil skin comes standard with stainless steel. The cabinet is protected by a durable epoxy powder coat paint. Designed with the operator in mind, operating instructions and warnings are both multi-lingual and illustrated. The control panel is ideally positioned for easy access. This heavy-duty cleaning machine is ideal for use in manufacturing or even food processing facilities where hot water is needed for cleaning machinery and equipment indoors. All models are certified to the rigid UL-1776 safety standards.



MODEL	GPM	PSI	HP	VOLT/PH	AMP	FUEL	PUMP	DRIVE	HOSE	SHIP WT (lbs)
1812SS	5.9	2500	10	230/1	42	NG	Hotsy Triplex	Belt	50'	885
1812SS-208	5.9	2500	10	208/1	48	NG	Hotsy Triplex	Belt	50'	885
1822SS	5.9	2500	10	230/3	28	NG	Hotsy Triplex	Belt	50'	870
1822SS-208	5.9	2500	10	208/3	33	NG	Hotsy Triplex	Belt	50'	870
1825SS	5.9	2500	10	460/3	14	NG	Hotsy Triplex	Belt	50'	885
1836SS	5.9	2500	10	575/3	11	NG	Hotsy Triplex	Belt	50'	885
1852SS	4.7	3000	10	230/1	42	NG	Hotsy Triplex	Belt	50'	885
1852SS-208	4.7	3000	10	208/1	48	NG	Hotsy Triplex	Belt	50'	885
1855SS	4.7	3000	10	460/3	14	NG	Hotsy Triplex	Belt	50'	870
1856SS	4.7	3000	10	575/3	11	NG	Hotsy Triplex	Belt	50'	885
1862SS	4.7	3000	10	230/3	28	NG	Hotsy Triplex	Belt	50'	880
1862SS-208	4.7	3000	10	208/3	33	NG	Hotsy Triplex	Belt	50'	770

OPTIONS		OPTIONS	
PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
280495	Primary Remote Station (1st Remote)	280515	Remote Soap Option—Requires Remote Station Option, use on first remote station. Purchase additional switch—PN 875985, and field wire for each additional remote station.
216722	Additional Remote Station(s). Use for Additional Remotes After Primary Remote. Purchase of Primary Remote required.	480284	LP Conversion Kit (Factory Installed)
480241	Auto Start/Stop Kit (Factory Installed)	835525	10" Natural Gas- or LP Gas-Fired Draft Diverter

5700 SERIES



S5732-4

- Oil or Natural Gas-Fired
- Belt-Drive Hotsy Pump with 7-Year Warranty

- 15 HP Baldor Motor ■ Electronic Ignition ■ Time Delay Shutdown ■ Thermal Shutdown ■ 24-Volt Control

The **5700 Series** produces a punch like few other indoor or outdoor high-pressure cleaning machines. With its 15 HP Baldor motor driving the incomparable Hotsy Pump, backed by a 7-year warranty, the 5700 Series delivers cleaning power of up to 7.8 GPM and 3000 PSI. It is designed specifically to add up to four remote operating stations. The painted cabinet is protected by a durable epoxy powder coat finish. The control panel is positioned for easy operator access. This heavy-duty cleaning machine is ideal for cleaning indoors or outdoors with hot water and can be outfitted to heat with oil, diesel or natural gas. All models are certified to the rigid UL-1776 safety standards.



MODEL	GPM	PSI	HP	VOLT/PH	AMP	FUEL	PUMP	DRIVE	PORTABILITY	HOSE	SHIP WT (lbs)
S5730-3	7.8	3000	15	230/3	47	Oil	Hotsy Triplex	Belt	Optional	50'	1060
S5733-1	7.8	3000	15	460/3	25	Oil	Hotsy Triplex	Belt	Optional	50'	1070
S5730-5	7.8	3000	15	208/3	50	Oil	Hotsy Triplex	Belt	Optional	50'	1060
S5732-5	7.8	3000	15	208/3	42	NG	Hotsy Triplex	Belt	N/A	50'	985
S5732-4	7.8	3000	15	230/3	45	NG	Hotsy Triplex	Belt	N/A	50'	985
S5735-3	7.8	3000	15	460/3	23	NG	Hotsy Triplex	Belt	N/A	50'	975

OPTIONS		OPTIONS	
PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
280495	Primary Remote Station (1st Remote)	280515	Remote Soap Option—Requires Remote Station Option, use on remote station. Purchase additional switch – PN 875985, and field wire for each additional remote station.
216722	Additional Remote Station(s). Use for Additional Remotes After Primary Remote. Purchase of Primary Remote required.	292699	Portagear, Models S5730-3, S5730-5, S5733-1
480241	Auto Start/Stop Kit (Factory Installed)	835525	10" Natural Gas-Fired Draft Diverter

GAS-ENGINE SERIES

- Oil-Fired
- 12 Volt DC
- Direct Drive
- 5 Battery-less Models
- 2 Electric-Start Models



871SS



781SS



921SS



965SS

The Gas Engine Series consist of the most compact and portable hot water pressure washers on the market. Powered by reliable gasoline engines, all you need is water and you can clean anywhere anytime. The seven models offer a broad range of cleaning power, from 2.5 to 3.8 GPM and from 2000 to 3500 PSI. All models (except 781SS) are backed by Hotsy's 7-year pump warranty and all are ETL safety certified.



1065SSE

MODEL	GPM	PSI	HP	ENGINE	BURNER	PUMP	DRIVE	PORTABILITY	HOSE	SHIP WT (lbs)
781SS*	2.5	2000	6	Robin	12V DC	Comet Axial	Direct	Std	50'	370
871SS*	2.7	2400	7	Robin	12V DC	Hotsy Triplex	Direct	Std	50'	370
921SS*	3.0	3000	9	Robin	12V DC	Hotsy Triplex	Direct	Std	50'	430
965SS*	3.0	3000	9	Honda	12V DC	Hotsy Triplex	Direct	Std	50'	450
1065SS*	3.5	3000	11	Honda	12V DC	Hotsy Triplex	Direct	Std	50'	495
1065SSE†	3.5	3000	11	Honda	12V DC	Hotsy Triplex	Direct	Std	50'	495
1075SSE†	3.8	3500	13	Honda	12V DC	Hotsy Triplex	Direct	Std	50'	500

*Battery not required †12V battery required, but not supplied E= Electric-start engine

1200 SERIES and Model 5645

- Gas-Powered
- Oil-Fired
- Belt Drive
- Electric-start



1260SS



1270SS Shown with optional Portage Kit



5645

The 1200 Series delivers some serious on-site, hot water cleaning capability of up to 6 GPM and 4000 PSI. Rugged gasoline engines all have electric start. Five models come with a 2000W generator. The self-contained cleaning units are built to hold up under the toughest of conditions. All feature the Hotsy pump, with its 7-year warranty and ETL safety certification (CSA-Certified for non-generator models).



MODEL	GPM	PSI	HP	ENGINE	BURNER	PUMP	DRIVE	PORTABILITY	HOSE	SHIP WT (lbs)
1260SS	4.3	3000	16	Vanguard	12V DC	Hotsy Triplex	Belt	Optional	50'	780
1260SSG*	4.3	3000	16	Vanguard	120V AC	Hotsy Triplex	Belt	Optional	50'	810
1270SS	4.5	4000	20	Honda	12V DC	Hotsy Triplex	Belt	Optional	50'	840
1270SSG*	4.5	4000	20	Honda	120V AC	Hotsy Triplex	Belt	Optional	50'	870
1280SS	5.2	3500	20	Honda	12V DC	Hotsy Triplex	Belt	Optional	50'	840
1280SSG*	5.2	3500	20	Honda	120V AC	Hotsy Triplex	Belt	Optional	50'	870
1290SS	5.6	3000	20	Honda	12V DC	Hotsy Triplex	Belt	Optional	50'	840
1290SSG*	5.6	3000	20	Honda	120V AC	Hotsy Triplex	Belt	Optional	50'	870
5645*	6.0	3000	24	Honda	120V AC	Hotsy Triplex	Belt	Optional	50'	1110

*Models include a 2000W Generator †12V battery is required for all models, but is not supplied

OPTIONS

PART NO.	DESCRIPTION
280199	Portage Kit, Models 1260SS, 1260SSG, 1270SS, 1270SSG, 1280SS, 1280SSG, 1290SS and 1290SSG
292699	Portage Kit, Model 5645

9400 SERIES Heating Modules

The 9400 Series heating modules give customers the flexibility to "convert" a cold water pressure washer into a hot water unit. By attaching the heating module to a cold water pressure washer the pressurized water is now heated to produce all the benefits of hot water cleaning. The four models use fuel oil, diesel or natural gas to heat the water using Hotsy's high-efficiency, vertical heating coil.



MODEL	GPM (Max)	GPM (Min)	VOLT/PH	AMP	BTU/HOUR	FUEL	SHIP WT (lbs)
9450	10	6	115/1	8	620,000	Oil-Fired	525
9452	10	6	115/1	1	540,000	Natural-Gas-Fired	500
9460	10	6	115/1	8	920,000	Oil-Fired	920
9462	10	6	115/1	1	920,000	Natural-Gas-Fired	935

OPTIONS	
PART NO.	DESCRIPTION
480291	Natural-Gas to LP Conversion for Model 9452 (Factory Installed)
480290	Natural-Gas to LP Conversion for Model 9462 (Factory Installed)
835525	10" Natural Gas-Fired Draft Diverter for Model 9452
835531	12" Natural Gas-Fired Draft Diverter for Model 9462

Fuel-burner types available:

- Diesel ■ Kerosene ■ Home Heating Oil
- Natural Gas ■ Propane (Optional)

Hotsy Hot-Water Pressure Washers

Exceptional quality, high reliability and advanced features make Hotsy the industry's first choice in hot-water pressure washers.

One look at Hotsy Hot-Water Pressure Washers tells you these are rugged, industrial-grade machines designed to give long life, high productivity and superior cleaning power.

As an industry leader and integrated manufacturer of pressure washers, Hotsy builds its own pumps, gun jets, valves and other key components critical to the long life and smooth operation of a Hotsy pressure washer.

After examining Hotsy's rugged designs and unique features, your customers will be convinced that a Hotsy Hot-Water Pressure Washer is the right machine for the job.

Seven-year limited warranty on Hotsy pumps—the best in the industry—protects this vital component.



ETL certification to UL 1776 standards meets stringent bid and application requirements.



Upright burner design provides maximum efficiency for fast heating, easy venting in indoor applications, plus excellent fuel economy.

- Upright burner design
- Industry's best heat exchanger
- Easy service design, accessible components
- Hotsy designed & specified components

BD SERIES

BELT DRIVE

BD Series shown in large cage (4-wheel) version. Small cage 2-wheel version also available.



The **BD Series** is the most rugged cold water pressure washer on the market with its all-steel frame and cage, Hotsy belt-drive, triplex pump and cleaning power of up to 5000 PSI. Four gas models make up what is Hotsy's most durable cold water line-up ever.

- Honda or Vanguard engine
- Small & Large Roll Cage design with lifetime warranty
- Totally enclosed belt guard
- 13" tubed pneumatic tires for easy handling
- Plated steel high-pressure wand w/ side handle
- ETL certified to UL-1776 safety standards



MODEL	GPM	PSI	HP	ENGINE	PUMP/MODEL #	DRIVE	FRAME	NO. WHEELS	HOSE	SHIP WT (lbs)
BD-373539	3.7	3500	13	Honda GX	Hotsy Triplex	BELT	Small Cage	2	50'	290
BD-404029	4.0	4000	16	Vanguard	Hotsy Triplex	BELT	Large Cage	4	50'	360
BD-405039E*	4.0	5000	20	Honda GX	Hotsy Triplex	BELT	Large Cage	4	50'	417
BD-455039E*	4.5	5000	24	Honda GX	Hotsy Triplex	BELT	Large Cage	4	50'	430

*E = Electric Start

OPTIONS

PART NO.	DESCRIPTION
35-356	E-Zee Hose Reel Kit*100' (small cage)
35-357	E-Zee Hose Reel Kit*100' (large cage)

OPTIONS

PART NO.	DESCRIPTION
35-360	5000 PSI Hose Reel Kit* (large cage)
35-362	5000 PSI Dual Hose Reel Kit,** (large cage)

BX SERIES

BELT DRIVE

BX Series shown with optional hose reel & mounting kit.



The **BX Series** is the similarly rugged, but more compact, line of belt-drive cold water pressure washers. Powered by Honda GX engines, the BX series delivers cleaning of up to 3500 PSI and an all-steel frame protected by a durable powder coat finish. Hotsy pumps carry a 7-year warranty.

- Honda GX engines, 5.5 to 13 HP
- Steel frame with lifetime warranty
- Totally enclosed belt guard
- 13" tubed pneumatic tires for easy handling
- Insulated steel high-pressure wand w/ side handle
- ETL certified to UL-1776 safety standards



MODEL	GPM	PSI	HP	ENGINE	PUMP/MODEL #	DRIVE	HOSE	SHIP WT (lbs)
BX-282039	2.8	2000	5.5	Honda GX	Hotsy Triplex	BELT	50'	152
BX-252739	2.5	2700	6.5	Honda GX	Hotsy Triplex	BELT	50'	160
BX-303039	3.0	3000	9	Honda GX	Hotsy Triplex	BELT	50'	222
BX-373539	3.7	3500	13	Honda GX	Hotsy Triplex	BELT	50'	261

OPTIONS

PART NO.	DESCRIPTION
35-350	EZ Hose Reel Kit 100' (incl. reel & mounting hardware)

DB SERIES

DIRECT DRIVE

DB Series shown with optional hose reel & mounting kit.



The **DB Series** is the most compact, affordable alternative, in the cold water line featuring a direct-drive pump. All five models are powered by reliable Honda engines. Light-weight design and tubed pneumatic tires make for easy maneuvering.

- Honda GC or GX engines, 5 to 13 HP
- Steel frame with lifetime warranty
- 10" tubed pneumatic tires for easy handling
- Protected by a powder coat finish
- Insulated, 2-piece steel high-pressure wand
- ETL certified to UL-1776 safety standards



MODEL	GPM	PSI	HP	ENGINE	PUMP/MODEL #	DRIVE	HOSE	SHIP WT (lbs)
DB-232336	2.3	2300	5	Honda GC	Comet/Axial AXD2527G	DIRECT	30'	130
DB-232439	2.3	2400	5.5	Honda GX	Hotsy Triplex	DIRECT	50'	140
DB-252739	2.5	2700	6.5	Honda GX	Hotsy Triplex	DIRECT	50'	145
DB-303039	3.0	3000	9	Honda GX	Hotsy Triplex	DIRECT	50'	175
DB-383539	3.8	3500	13	Honda GX	Hotsy Triplex	DIRECT	50'	194

OPTIONS

PART NO.	DESCRIPTION
35-352	EZ Hose Reel Kit 100' (incl. reel & mounting hardware)

1700 SERIES

BELT DRIVE



Shown with optional stainless steel cabinet

The **1700 Series** offers the most reliable stationary, electric-powered, cold water pressure washer featuring a Hotsy belt-drive pump with 7-year warranty, insulated variable pressure wand and ETL safety certification.



- Baldor electric motor, 2-10 HP
- Hotsy pump with 7-year warranty
- Downstream detergent injector
- Insulated SS variable pressure wand
- Hot Water Seal Kit standard
- Option-ready for time delay shutdown or automatic stop-start.

MODEL	GPM	PSI	HP	VOLT/PH	AMPS	PUMP/MODEL#	DRIVE	PORTABILITY	HOSE	SHIP WT (lbs)
1710	2.75	1000	2	120/1	20	Hotsy Triplex	BELT	Optional	50'	200
1720	3.9	2000	6	230/1	28	Hotsy Triplex	BELT	Optional	50'	275
1722	3.9	2000	6	208/1	30	Hotsy Triplex	BELT	Optional	50'	240
1723	3.9	2000	6	208/3	16	Hotsy Triplex	BELT	Optional	50'	250
1724	3.9	2000	6	230/3	14.4	Hotsy Triplex	BELT	Optional	50'	250
1725	3.9	2000	6	460/3	7.2	Hotsy Triplex	BELT	Optional	50'	250
1730	3.46	3000	7.5	230/1	36	Hotsy Triplex	BELT	Optional	50'	280
1732	3.46	3000	7.5	208/1	38	Hotsy Triplex	BELT	Optional	50'	280
1733	3.46	3000	7.5	208/3	23	Hotsy Triplex	BELT	Optional	50'	280
1734	3.46	3000	7.5	230/3	21.5	Hotsy Triplex	BELT	Optional	50'	280
1735	3.46	3000	7.5	460/3	11	Hotsy Triplex	BELT	Optional	50'	270
1740	4.76	3000	10	230/1	45	Hotsy Triplex	BELT	Optional	50'	305
1742	4.76	3000	10	208/1	45	Hotsy Triplex	BELT	Optional	50'	305
1743	4.76	3000	10	208/3	29	Hotsy Triplex	BELT	Optional	50'	302
1744	4.76	3000	10	230/3	26.8	Hotsy Triplex	BELT	Optional	50'	300
1745	4.76	3000	10	460/3	13.5	Hotsy Triplex	BELT	Optional	50'	315
1750	5.93	2500	10	230/1	45	Hotsy Triplex	BELT	Optional	50'	320
1752	5.93	2500	10	208/1	45	Hotsy Triplex	BELT	Optional	50'	320
1753	5.93	2500	10	208/3	29	Hotsy Triplex	BELT	Optional	50'	320
1754	5.93	2500	10	230/3	26.8	Hotsy Triplex	BELT	Optional	50'	310
1755	5.93	2500	10	460/3	13.5	Hotsy Triplex	BELT	Optional	50'	310

OPTIONS	1700 SERIES
PART NO.	DESCRIPTION
280700	Kit, 1700 Wheel w/Chemical Rack
280701	Kit, 1700 Wall Mount
280702	Kit, 1700 Floor Stand, Tall (20 3/4"W x 29"D x 36"H)
280703	Kit, Caster Wheels for 1700 Floor Stand
280704	Kit, Hose Reel w/Bracket, 1700 Stand & Wall Mount Kits
280705	Kit, 1700 Floor Stand, Short (20 3/4"W x 29"D x 24"H)
280712	Kit, 1700 Wall Mount, Stainless Steel
280710	Time Delay Shut Down, For 172x, 173x & 174x Models (Factory Installed)
280714	Time Delay Shut Down for 1710 (Factory Installed)
280713	Time Delay Shut Down for 175x Models (Factory Installed)
280711	Stainless Steel Base & Cover, 1700 Series (Factory Installed)
280717	Automatic Stop/Start for 1710 & 172x Models
280718	Automatic Stop/Start for 175x Models
280715	Automatic Stop/Start for 173x & 174x Models)



Model 1710 shown with optional wheel kit (PN 280700).



1700 Series shown with optional hose reel kit, (PN 280704), cart (PN 280702), caster wheel kit (PN 280703) and stainless steel base and cover (PN 280711).

EP SERIES

DIRECT DRIVE



The **EP Series** offers a portable alternative to the electric-powered, cold water pressure washer line featuring the Hotsy direct-drive pump with a 7-year warranty. The EP's functional design is further enhanced by 10" tubed pneumatic tires, a convenient hose-and-gun rack and ETL safety certification.



- 1725 RPM Baldor electric motor
- Steel frame with lifetime warranty
- Hotsy pump with 7-year warranty
- Insulated wand and fatigue-free gun
- Powder coat finish protection
- ETL safety certification

MODEL	GPM	PSI	HP	VOLT/PH	AMPS	PUMP / MODEL #	DRIVE	HOSE	SHIP WT (lbs)
EP-201009D	2.0	1000	1.5	120/1	15	Hotsy Triplex	DIRECT	50'	151
EP-301009D	3.0	1000	2	120/1	20	Hotsy Triplex	DIRECT	50'	163
EP-301509A	3.0	1500	3	230/1	15	Hotsy Triplex	DIRECT	50'	157
EP-352009A	3.5	2000	5	230/1	20	Hotsy Triplex	DIRECT	50'	210

OPTIONS	EP SERIES
PART NO.	DESCRIPTION
35-354	EZ Hose Reel Kit 100' (incl. reel & mounting hardware)

HAND-HELD COLD WATER PRESSURE WASHERS

ET SERIES

Electric-Powered

DIRECT DRIVE



The **ET Series** provides a light-weight, hand-held alternative to the electric-powered line offering many of the same features that have distinguished the Hotsy name over the years, featuring a reliable direct-drive pump and ETL safety certification.



- Baldor electric motor, 1.5 - 2 HP
- Comet axial high-pressure pump
- Cleaning power of up to 1400 PSI
- Weighs as little as 80 lbs.
- Lifetime warranty on frame
- Convenient carrying handle

MODEL	GPM	PSI	HP	VOLT/PH	AMPS	PUMP/MODEL #	DRIVE	HOSE	SHIP WT (lbs)
ET-201006D	2.0	1000	1.5	120/1	15	Comet AXD2020E	DIRECT	30'	90
ET-201406D	1.8	1400	2	120/1	20	Comet AXD2020E	DIRECT	30'	103

HC SERIES

Gasoline-Powered

DIRECT DRIVE



The **HC Series** is the hand-held model of the gasoline-powered line, delivering cleaning capability of up to 2400 PSI. Both models are driven by Honda engines and feature reliable direct-drive pumps and are ETL safety certified.



- Honda engines, 5 - 5.5 HP
- Direct-drive high-pressure pumps
- Cleaning power of up to 2400 PSI
- Weighs as little as 70 lbs.
- Lifetime warranty on frame
- Convenient carrying handle

MODEL	GPM	PSI	HP	ENGINE	PUMP/MODEL #	DRIVE	HOSE	SHIP WT (lbs)
HC-232336	2.3	2300	5	Honda GC	Comet/Axial	DIRECT	30'	74
HC-232439	2.3	2400	5.5	Honda GX	HotsyTriplex	DIRECT	30'	108